PezzoL



THOR

204BB-01 S3 CI SRC

Standard EN ISO 20345:2011

DGUV 112-191

Sizes 37-47

Thinsulate® B200 is a lightweight and thin lining material for outstanding thermal insulation, that keeps the feet warm in extreme weather conditions.

Reflective material.

ICON dual density polyurethane sole designed for excellent performance on wettest and driest grounds. This sole has been tested for slip-resistance in the SATRA laboratories on metal grating and wood scaffold board.



DUAL DENSITY PU ICON

- SRC Slip resistance sole.
- Self-cleaning cleated sole
- Fuel oil resistance sole
- Wide fit for maximum stability and protection.
- Tacco ammortizzante.



SRC Slip resistance A Antistatic P Perforation resistance Resistant to an impact of 200 Joules and compression of 15Kn E Energy absorption at the heel part FO Fuel oil resistance sole WRU Water penetration resistant upper CI Cold insulation of the sole

Esolight 1.0 polyurethane midsole with reinforced Over cap. The low-density micro-cell polyurethane increase energy absorption, while the outsole is made by highdensity Esolight polyurethane to guarantee durability and slip resistance.

PZX fiberglass toe cap and anti-puncture Txzero textile insert for extreme lightness, protection and flexibility.



T-01

FIBER

- Anatomic insole for more comfort
- Supporting PU foam = Dissipation and **Energy Return**
- Fully lined with conductive microperforated fabric to reduce foam wearing